SCIENTIFIC INDUSTRIES SUGGESTED CATALOG COPY Suggested Category: Rotators, Rockers, Shakers

ROTO-SHAKE GENIE®—Rotate, rock, or 3-D orbit any container!

The Roto-Shake Genie is designed to provide rotating, rocking, and 3-D orbital shaking in one compact, durable and user-friendly unit. It is ideal for mixing or washing of any sample type in virtually any container.

Easily and quickly converts from rocking to rotating or vice versa.

Deceriation

- Magnetic stainless steel platform and clip plate system holds almost any container.
- Economical and Space-Saving.
- Ideal for Cold Rooms and Incubators.
- Maintains set speed between 0-38°C.

ORDERING INFORMATION

Catalag Na

Catalog No.	Description
SI-1100	Roto-Shake Genie, 120V
SI-1101	Roto-Shake Genie, 230V, No Plug
0A-1100-070	Non-Skid Tray for Roto-Shake Genie
SI-1120	6 Clip Plates for 12 each 10-13mm tubes
SI-1121	6 Clip Plates for 6 each 15-17mm tubes
SI-1122	6 Clip Plates for 3 each 28-30mm tubes
SI-1123	1 Clip Plate for 12 each 10-13mm tubes
SI-1124	1 Clip Plate for 6 each 15-17mm tubes
SI-1125	1 Clip Plate for 3 each 28-30mm tubes
SI-1126	Magnetic Bag Mounting Strips (pack of 16)
SI-1127	Expansion Kit (two stainless steel trays,
	24 magnetic bag mounting strips)
SI-1130	2 Clip Plates for Hybridization Tubes
SI-1134	2 Universal Clip Plates
SI-1135	1 Magnetic Covered 100 Microtube Box
SI-1136	1 Clip Plate for 100ml Volumetric Flasks
SI-1150	3-D Orbital Shaker Attachment for Roto-Shake Genie
SI-1170	Stackable Tray
SI-1175	Horizontal Orbital Shaker Attachment for Roto-Shake Genie

SPECIFICATIONS

SI-1320

Magnetic Platform, 1 Clip Plate each for 10-13mm, 15-17mm, and 28-30mm Tubes, 4 Magnetic Bag Mounting Strips, Supplied with

and Non-Skid Tray.

Magnetic Platform

5-35 RPM Rotating

10-70 cycles per minute Rocking Rocking Angle ±10 degrees from horizontal Dimensions 252 x 508 x 267mm (D x W x H)

(9.9 x 20 x 10.5in)

Depth with Rocker Tray - 305mm (12in)

4.5 Kg (10 lb) Platform Capacity Weight 11.8 Kg (26 lb) "Installation Category 2" Environmental

0-38°C (32-100°F)

95% maximum relative humidity Warranty 2-year manufacturer warranty